## IN THE CLAIMS

Please cancel claims 10, 17, 18, and 21-24.

Please amend the following claims which are pending in the present application:

1. (Currently amended) An apparatus comprising:

a guiding enclosure to guide and keep energy from an energy source within the guiding enclosure, the guiding enclosure made of a material reflective of the energy from the energy source, the energy source being an electromagnetic radiation source;

a supporting piece detachably coupled with the guiding enclosure, the supporting piece made of a material transparent to the energy from the energy source; and

an absorbing piece coupled to and supported by the supporting piece within the guiding enclosure, the absorbing piece made of at least one material that absorbs the energy from the energy source and transfers the energy to an object to be heated, a predetermined composition of the absorbing piece controlling an energy absorption rate of the absorbing piece. piece; and

a holder with a top portion contacting a bottom portion of the guiding enclosure to keep the energy from the energy source within the guiding enclosure.

Inventor(s): Song-Hua Shi, et al. Application No.: 10/002,893

- 2. (Original) The apparatus of claim 1 wherein the predetermined composition of the absorbing piece includes the absorbing piece made of one material that uniformly absorbs the energy from the energy source.
- 3. (Original) The apparatus of claim 1 wherein the predetermined composition of the absorbing piece includes more than one material, each material capable of absorbing the energy from the energy source at a different absorption rate.
- 4. (Currently amended) The apparatus of claim 1 wherein [[a]] the energy source is [[the]] a microwave source.
  - 5. (Original) The apparatus of claim 4 wherein the guiding enclosure material is made of metal.
  - 6. (Original) The apparatus of claim 4 wherein the supporting piece material is selected from the group consisting of microwave transparent ceramic and quartz.
  - 7. (Original) The apparatus of claim 4 wherein the absorbing piece material is selected from the group consisting of silicon, carbon doped metal, and microwave absorbing ceramics.

Inventor(s): Song-Hua Shi, et al. Application No.: 10/002,893

8. (Cancelled)

9. (Currently amended) The apparatus of claim 8 claim 1 wherein the

energy source is an infrared source and the supporting piece material is selected

from the group consisting of quartz, potassium bromide, and infrared transparent

glass.

10. (Cancelled)

11. (Original) The apparatus of claim 1 wherein the object to be heated

includes a plurality of solder joints sandwiched between a substrate and a chip.

12. (Original) The apparatus of claim 11 wherein the object to be heated

further includes an underfill material surrounding the solder joints, the solder joints

reflowing from the energy before the underfill material is cured by the energy.

13. (Original) The apparatus of claim 12 wherein the object to be heated

further includes a material sandwiched between the chip and a heat sink on a side of

the chip opposite of a side of the chip facing the substrate.

Inventor(s): Song-Hua Shi, et al. Application No.: 10/002,893

14. (Original) The apparatus of claim 13 wherein the object to be heated further includes a heat sink sealant material sandwiched between the heat sink and the substrate at two contact points where the heat sink contacts the substrate, the material cured by the energy before the heat sink sealant material gels from the energy.

15. (Currently amended) The apparatus of claim 14 wherein the object to be heated further includes a material sandwiched between the heat sink and [[a]] the chip.

16. (Currently amended) An apparatus comprising:

a guide having an internal cavity, an end through which energy from an electromagnetic radiation source can enter the cavity, and a mouth on a side of the cavity opposing the end, the guide being made of a material reflective to the energy so that a majority of the energy is guided to the mouth;

a support piece secured over the mouth and being made of a material through which a first portion of the energy transmits; and

an absorbing piece being made of at least one material which absorbs a second portion of the energy through a first surface thereof facing into the cavity to cause heating thereof, the heat being transferred from a second surface thereof against which an object to be heated can be located, the absorbing piece having a

Inventor(s): Song-Hua Shi, et al. Application No.: 10/002,893

<u>predetermined composition that includes more than one material, each material</u>

<u>capable of absorbing the energy at a different absorption rate.</u>

17 - 18. (Cancelled)

19. (Previously presented) The apparatus of claim 16 wherein the energy is from a microwave source.

20. (Cancelled)

21-24. (Cancelled)

26 25. (New) An apparatus comprising:

a guiding enclosure to guide and keep energy from an energy source within the guiding enclosure, the guiding enclosure made of a material reflective of the energy from the energy source, the energy source being an electromagnetic radiation source;

a supporting piece detachably coupled with the guiding enclosure, the supporting piece made of a material transparent to the energy from the energy source; and

an absorbing piece coupled to and supported by the supporting piece within the guiding enclosure, the absorbing piece made of at least one material that absorbs the energy from the energy source and transfers the energy to an object to be heated, a predetermined composition of the absorbing piece controlling an energy

Inventor(s): Song-Hua Shi, et al. Application No.: 10/002,893

absorption rate of the holding piece and including more than one material, each material capable of absorbing the energy from the energy source at a different absorption rate.

27 26. (New) A method comprising:

positioning an object for heating within a chamber having an electromagnetic radiation source such that the object is in alignment with an absorbing piece secured by a supporting piece, the supporting piece made of a material transparent to the energy from the electromagnetic radiation source;

B

guiding and confining the energy from the electromagnetic radiation source within a guiding-enclosure inside the chamber so that all of the energy is guided at the absorbing piece and the object, the guiding enclosure made of a material reflective of the energy from the electromagnetic radiation source; and

transferring the energy from the absorbing piece to the object by having the absorbing piece be made of at least one material that absorbs the energy from the electromagnetic radiation source for transfer to the object, a predetermined composition of the absorbing piece controlling an energy absorption rate of the absorbing piece, the predetermined composition of the absorbing piece including more than one material, each material capable of absorbing the energy from the energy source at a different absorption rate.

Inventor(s): Song-Hua Shi, et al. Application No.: 10/002,893

2728 (New) The method of claim 26 wherein the electromagnetic radiation source is a microwave source.

BA

Inventor(s): Song-Hua Shi, et al. Application No.: 10/002,893